



## Easy Clean

Conforms to ISI/IGBC & GRIHA Specifications



**Product composition:** Easy Clean luxury emulsion has been formulated with special types of cross-linking polymers and fine pigments. It is formulated in a balanced manner with properties like dispersion, sheen level, anti-fungal, anti-fading and minimum porosity. It also provides high washability and is easy to maintain. It maintains its fresh look for years. It gives a smooth sheen finish at an affordable price.

**USP:** Soft sheen, non-stick paint film with very high washability and scrub resistance, giving it a longer life and easy maintenance. It is free from any heavy metal like lead, mercury and chromium.

**Usage area:** On plastered surfaces.

### DIRECTIONS FOR USE

**Surface preparation:** For fresh/ new surfaces, sand the surface with Emery Paper No.80 and wipe clean. Apply the first coat of primer and allow it to dry for 6 to 8 hours. Smoothen the surface by applying thin coats of putty to fill in all the dents. Allow the putty to dry overnight. Sand the surface with Emery Paper No.100 and wipe clean. Apply the second coat of primer and allow it to dry for 6 to 8 hours. Sand the surface with Emery Paper No.220 and wipe clean.

**For previously painted surfaces:** Strip all the old paint and remove all the loose particles before starting the above process.

**Directions for application:** Dilute the paint as per the recommended dilution ratio. Apply the first finishing coat and allow it to dry for at least 6 to 8 hours. After the first coat dries, apply the second coat and allow it to dry overnight.

### COVERAGE\*

All in 1 coat primed and smooth surface	No. of coats	New surface
Brush Application	2 coats	120-130 sq ft
Roller Application	2 coats	120-130 sq ft

\*It depends on many factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc. The coverage mentioned is under ideal conditions and will vary depending on site conditions.

### RECOMMENDED UNDERCOATS

Primers
For walls or plastered surfaces – BP Cement Primer WT (Alkali Resistant)
Putty
For walls or plastered surfaces – Bison Wall Putty

### PACKS

White and P0	ColorBank	Bases (ColorBank)	Offered shade range
1 ltr, 4 ltr, 10 ltr, 20 ltr	0.9 ltr, 3.6 ltr, 9 ltr, 18 ltr	P0, W1, N2, Yellow, Red	Over 2000 shades

## TECHNICAL DATA

1	<b>Recommended Thinner</b>	Potable water	6	<b>Drying Time</b>	SD: 20-30 minutes depending on weather conditions. HD: 6-8 hours
2	<b>Recommended Surfaces</b>	Sand/cement plaster surface, asbestos, brickwork, concrete block and fiberboard.	7	<b>Gloss Level</b>	5 - 15 at 60° GH/ 35-50 at 85° GH on a glass plate when released at 300 micron DFT applied by box coater.
3	<b>Method of Application</b>	Brush, roller or spray	8	<b>Flash Point</b>	100% water-based paint, hence NR
4	<b>Dilution Ratio</b>	For brush application 400 ml of water/ltr of emulsion.  <small>Note: In case of N Base shades, no dilution is advised to ensure proper colour depth.</small>	9	<b>Fire Hazard Class</b>	Non-flammable
5	<b>Number of Coats Required</b>	Apply 2 coats of Easy Clean Luxury Emulsion for re- painting provided the colour is same. For fresh painting it is advisable to give 3 coats for a rich look.	10	<b>Pot life of Thinned Material</b>	Overnight
			11	<b>VOC</b>	47 gm/ltr
			12	<b>Density</b>	Depends on the bases
			13	<b>Certification</b>	IS:15489
			14	<b>Safety Data</b>	Refer MSDS

## SPECIAL NOTE

The paint film needs to set on the newly painted wall and hence should be allowed to dry completely for 15 days before it is washed or scrubbed. Apply this product on a zero undulated surface. Otherwise, surface defects will be visible as it is a sheen emulsion.

## POINTS TO NOTE

- Shake well before use and do not over dilute
- Keep the container tightly closed to prevent drying
- Use 1 coat of Bio-Wash for killing fungal growth
- Scrape off old paint thoroughly before painting starts
- Gyroshake well after tinting through CB machine
- For deeper shade apply 1 additional coat
- Do not apply paint on lime washed surfaces and damp wall
- In case of contact with eyes, wash immediately with water and seek medical advice

## CLEANING INSTRUCTIONS

- Use only a toilet soap to clean stains
- To clean oil based stains use mineral turpentine oil only
- Use only a soft white cotton cloth for cleaning
- While cleaning, wipe gently without using pressure
- Attempt cleaning the surface only after one week of application

Version No: BPP2/04/2016. Please note that this data sheet supersedes all previous versions.

### BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | CONSUMER RELATIONS MANAGER Ph: 1800-103-6030  
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com