



BISON GLOW

ACRYLIC INTERIOR EMULSION



Product Attributes



Sheen Finish
Imparts sheen finish to the walls

Smooth Finish



Green Pro Certified
Validates our effort in striving towards cleaner, more sustainable future


Product Description

Bison Glow acrylic emulsion is an economy emulsion paint which gives soft sheen finish at an affordable price. It is an interior paint with soft sheen finish.

Recommended Use

Plastered surfaces, concrete walls, asbestos, fiberboard, gypsum board and false ceilings.

Colour Range



Over 2000 shades

Finish

- HIGH
- MEDIUM
- SMOOTH
- SOFT SHEEN ✓

Soft sheen finish

Toxicity



VOC :35 gm/lit Max.
for Whites and Bases

Coverage



130-150 sqft/lit/2 coats, under ideal test conditions (Actual coverage may vary depending upon surface conditions, preparation, application and type of shade)

Recommended Dilution



Brush : 50 – 60% by volume
Roller : 45 – 55 % by volume
Auto Roller : 45 – 55 % by volume

Application Method



Brush / Roller / Spray

Recommended Thinner / Cleaner



Potable water

Gloss Level



4 -7 at 60 ° GH (depends on shade)
measured as per standard method

Drying Time



SD: 15 – 25 minutes at 60 % RH, 25°C
HD: 6 – 8 hours



BISON GLOW

ACRYLIC INTERIOR EMULSION



Packs



1 Ltr

4 Ltr

10 Ltr

20 Ltr



Fire Hazard Class
Water-based paint,
non-flammable



Pot Life of Thinned Material
Use within 24 hours

Surface Preparation




Remove all dirt, loose paint, flakes and dust particles using a wire brush



Cover fine cracks, holes, dents with putty, and large cracks may need cement work
Allow sufficient time for the putty/cement work to dry completely

Priming:



Apply 1 coat of BP Cement Primer / BP White Primer suitably diluted and dry it overnight
Application of Primer is mandatory.

Directions for Topcoat Application

Dilute 1 L of paint with 500 – 600 ml of potable water

Apply with brush / roller

Allow the paint film to dry for 6 – 8 hours and then apply the 2nd coat

Very light shades may require more than two coats for best performance

PRECAUTIONS

- Stir well and strain the diluted paint before use
- Do not over dilute or over extend brush
- Do not apply paint if the ambient temperature is less than or expected to fall below 10° C
- Use only Berger Paints machine colourants to tint shades
- Allow sufficient time for each coat to dry before next coat application
- Apply paint with Auto-roller for best performance

Version No: BPP1/09/2019. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com