



SILK GLOW

LUXURY INTERIOR EMULSION



Product Attributes



Water repellent

Flexible enough to cover hair-cracks



High opacity

High coverage



Low smell

Product Description

Silk Glow Luxury Emulsion is an interior wall paint designed to give your walls a durable premium, rich appearance. It is formulated with tailor-made 100% acrylic emulsion that retains the fresh glossy new look for a longer period. The product is free of added APEO, formaldehyde and is low on VOC.

Silk Glow comes in a range of shades to choose from which can give a unique premium look to the interiors.

VOC



30-35 gm/lt

Dilution Ratio



Brush : 40-50% by volume.

Roller : 35-40% by volume.

Deep shades from N base to be applied without dilution

Application Tools



Brush/ Roller/ Auto-roller

Coverage



130-150 sqft/lt/2 coats depending on shade, quality of surface preparation and application condition


Drying Time



SD: 15-25 min at 60% RH, 25°C

HD: 6-8 hours

Gloss/ Sheen



60° = 13-15; 85° = 45-55 (depending on shade, measured as per standard test method)

Flash Point



water based paint, hence non-flammable



SILK GLOW

LUXURY INTERIOR EMULSION



Areas of application

Plastered surfaces, concrete walls, fibre board, asbestos, gypsum board and false ceiling

APPLICATION DETAILS



Surface Preparation

Remove all dirt, loose paint, flakes using wire mesh. Cover fine cracks with putty, large cracks may need cement work. Allow sufficient time for the putty/cement work to dry.



Priming

Apply one coat of BP Cement Primer/ Seal-O-Prime suitably diluted and dry it overnight.



Top Coat

Mix well. Dilute with potable water and apply with brush or roller. Allow it to dry for at least 6-8 hours or overnight depending ambient temperature, humidity and surface conditions. Apply second coat only when the first coat is dry.
DO NOT OVERTHIN. DO NOT APPLY WHEN AMBIENT TEMPERATURE IS BELOW 10°C OR MORE THAN 40°C



Fire Hazard Class
Non- flammable



Stability of used paint
use within 24 hours

SAFETY DATA

Refer MSDS

ADDITIONAL INFORMATION

- No added lead, Chromium (VI), Mercury
- No added APEO, formaldehyde and ammonia

Version No: BPP1/04/2021. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com